

ITF COURT PACE CLASSIFICATION PROGRAMME

TECHNICAL DATA SHEET

Brand name	Pro DecoTurf		
Company Name	California Products Corp.		
Address	150 Dascomb Road Andover, MA 01810 USA		
Telephone	978-623-9980	Fax	978-623-9970
Email	info@decoturf.com	Website	www.decoturf.com

TECHNICAL DATA

GENERAL DESCRIPTION:

DecoTurf

Cushioned Tennis Surface of Champions

- ✓ **Surface of the US Open since 1978.**
- ✓ **Selected for use at the world's most prestigious tournaments, the 2004 and 2008 Olympic Games.**
- ✓ **Multi-layer cushion system affords maximum player comfort and exceptional durability.**
- ✓ **Consistent speed of play and true ball bounce.**
- ✓ **100% acrylic resins and deep rich pigments create vibrant long lasting colors.**
- ✓ **Highest quality products, low maintenance, outstanding customer service, and unparalleled overall customer value.**
- ✓ **Well established network of "Authorized Applicators" around the world.**

SPECIFICATION OF COURT SURFACE MATERIALS AND CONSTRUCTION, INCLUDING METHOD OF APPLICATION:

STANDARD ASPHALT INSTALLATION

New Construction • Level with Court Patch binder mix or Plexipatch
 1 coat Acrylic Resurfacer @ 0.06 gals sq. yd.
 3 coats DecoTurf II @ .48 gals sq. yd. total
 2 coats DecoBase II @ .24 gals sq. yd. total
 2 coats DecoBase I/ Color MP mix @ .12 gals sq. yd total
 2 coat DecoColor MP @ .08 gals sq.yd. total

STANDARD CONCRETE INSTALLATION

New Construction • Acid Etch with Concrete Preparer.
 Level with Court Patch Binder.
 Ti-Coat as Primer.
 1 coat Acrylic Resurfacer @ 0.06 gals sq. yd.
 3 coats DecoTurf II @ .48 gals sq. yd. total
 2 coats DecoBase II @ .24 gals sq. yd. total
 2 coats DecoBase I/ Color MP mix @ .12 gals sq. yd total
 2 coat DecoColor MP @ .08 gals sq.yd. total.

LINE MARKINGS:

Apply one coat of 100% Acrylic Deco Line Paint with a roller, brush or airless sprayer.

MAINTENANCE GUIDELINES:

Keep courts free of dirt or debris, wash with water monthly.

WARRANTY:

Extended warranties are available when the surface is installed by an Authorized Applicator of the Plexipave System. Materials are covered by a limited manufacturer's warranty.

Disclaimer. The ITF cannot be held responsible for, and accepts no liability for, the failure of any product or service manufactured, produced or provided according to the information given in this data sheet or for any acts or omissions made in reliance upon it or in connection with it.